

# Solis-3P10K-4G-AU

Solis 4G Three Phase Inverters



## Features:

- Solis 3P 4G Three Phase Range
- 160V-850V MPPT voltage range- ultra low startup
- Dual MPPT design with precise MPPT algorithm
- THDi<1.5%, low harmonic distortion against grid
- Over 98.7% Max. efficiency
- Multiple protections functions
- RS485, WiFi/LAN/GPRS (optional) interface
- WiFi monitoring available-plus access to Android and Apple apps

## Model:

Solis-3P10K-4G-AU

## Datasheet

Model Name	Solis-3P10K-4G-AU
<b>Input DC</b>	
Max. DC input power(kW)	15
Max. DC input voltage(V)	1000
Nominal DC voltage(V)	600
Start-up voltage(V)	180
MPPT voltage range(V)	160-850
Max. input current(A/B)	22A+22A
Max. Short Circuit current for each MPPT	34.3A+34.3A
MPPT number/ Max input strings number	2/4
<b>Output AC</b>	
Rated output power(kW)	10
Max. apparent output power(kVA)	11
Rated grid voltage(V)	400
Rated grid frequency(Hz)	50/60
Operation phase	Three Phase
Rated grid output current(A)	14.4
Max. output current(A)	15.9
Power Factor (at rated output power)	0.8leading ... 0.8lagging
THDi (at rated output power)	<1.5%
<b>Efficiency</b>	
Max. efficiency	98.7%
EU efficiency	98.1%
MPPT efficiency	>99.5%
<b>Protection</b>	
DC reverse-polarity protection	Yes
Insulation resistance monitoring	Yes
Residual current detection	Yes
Surge protection	Yes
Grid monitoring	Yes
Islanding protection	Yes
<b>General Data</b>	
Dimensions(mm)	563*310*219mm
Weight (kg)	18.9
Topology	Transformerless
Self consumption (night)	<1W (Night)
Operating ambient temperature range	-25~60°C
Relative humidity	0~100%
Ingress protection	IP65
Noise emission(typical)	<60 dBA
Cooling concept	Intelligent fan-cooling
Max. operation altitude	4000m
Grid connection standard	EN50549, AS4777, VDE0126-1-1, IEC61727, G98, G99
Safety/EMC standard	IEC62109-1/-2, AS3100, EN61000-6-1, EN61000-6-2, EN61000-6-3, EN61000-6-4
<b>Features</b>	
DRM	Yes
DC connection	MC4
AC connection	Terminal connectors
Display	LCD, 2x20 Z.
Communication connections	4 Pin RS485 connector
Monitoring	WiFi or GPRS
Warranty	5 years (extend to 20 years)

# Solis-1P5K-4G

Solis 4G Single Phase Inverters



## Features:

- ▶ Solis 1P 4G Single Phase Range
- ▶ High frequency switching technology - Smaller, smarter
- ▶ 24-hour load consumption monitoring
- ▶ Dual MPPT design with precise MPPT algorithm
- ▶ Integrated Export Power Manager(EPM)
- ▶ Over 98.1% Max. efficiency
- ▶ RS485, WiFi/LAN/GPRS (optional) interface
- ▶ WiFi monitoring available-plus access to Android and Apple apps

## Model:

Solis-1P5K-4G

## Datasheet

Model Name	Solis-1P5K-4G
<b>Input DC</b>	
Max. DC input power(kW)	6.7
Max. DC input voltage(V)	600
Nominal DC voltage(V)	330
Start-up voltage(V)	120
MPPT voltage range(V)	90-520
Max. input current(A/B)	11A+11A
Max. Short Circuit current for each MPPT	17.2A+17.2A
MPP number/Max input strings number	2/2
<b>Output AC</b>	
Rated output power(kW)	5
Max. apparent output power(kVA)	5
Rated grid voltage(V)	230
Rated grid output current(A)	21.7
Max. output current(A)	25A(21.7 for AUS)
Power Factor (at rated output power)	0.8leading ... 0.8lagging
THDi (at rated output power)	<3%
DC injection current	<0.5%In
<b>Efficiency</b>	
Max. efficiency	98.1%
EU efficiency	97.3%
MPPT efficiency	>99.5%
<b>Protection</b>	
DC reverse-polarity protection	Yes
Insulation resistance monitoring	Yes
Residual current detection	Yes
Surge protection	Yes
Islanding protection	Yes
Integrated DC switch	Optional
<b>General Data</b>	
Dimensions(mm)	310W*543H*160D
Weight (kg)	11.5
Topology	Transformerless
Self consumption (night)	<10W (Night)
Operating ambient temperature range	-25~60°C
Relative humidity	0~100%
Ingress protection	IP65
Noise emission(typical)	<20dBA
Cooling concept	Natural convection
Max. operation altitude	4000m
Designed lifetime	>20 years
Grid connection standard	EN505049, AS4777.2:2015, VDE0126-1-1, IEC61727, VDE N4105, G98, G99, IEC 62116
Safety/EMC standard	IEC62109-1/-2, NB/T 32004, EN61000-6-2, EN61000-6-3
<b>Features</b>	
DC connection	MC4
AC connection	IP67 rated plug
Display	LCD, 2x20 Z.
Communication connections	4 pins RS485 connector
Monitoring	WiFi or GPRS
Warranty	5 years standard (extend to 20 years)
DRM function for AUS	Integrated DRM function for AUS